







SPECIFICATIONS UPS HD-2000

Front panel:	Model (2000VA/1200W)	HD-2000(3 steps of AVR, CPU controlled)
LCD indicator 	Display	LCD Indicator
	Input voltage range	145-290Vac
	Output voltage range	200-255+/-5Vac
	Output frequency	50±0.5Hz (DC Mode)
	Wave form	Modified sine wave
	Transfer time	≅ 10ms
	Capacity & quantity of battery	4pcs*12V7AH(Optional)
	Charging period	10-16/ hours
	Backup time	3-20/minutes (1PC+15 inch CRT)
	Rear panel:	Transformer size & material
	RJ45/11 & USB	Yes
	Auto re-starts when AC recovers	Yes
	Silence setup	Yes
	Automatic charging (offline charging)	Yes
	Battery low voltage protection	Yes
	Overload & Short circuit protection	Yes
	Product dimension (mm)	220*145*405
	Color box dimension (mm)	480*226*320
Power cord:	Master box dimension (mm)	495*238*343
 P-03	Pcs in one master carton	1
	Gross weight (1pc, kg)	21.5
	Net weight (1pc, kg)	20.5
Optional accessories:	(20'contai ner) / Loading capacity (20' ctrn)	600pcs
01 [-Megatec Software cable & CD] 	<input checked="" type="checkbox"/> (40'contai ner) / Loading capacity (40' GP)	1450pcs

